

Race Number:	 	
Name:	 	

Utah SBA Tech Inspection Checklist

Numbers			Racer Check	Tech Check
	Front			
	Tail, Side or Lower			
	Black Numbers 6"	Tall (White Background for Experts or Yellow for Novice)		
Safety Wir	е			
-	Oil Drain Bolt	(including upper oil galley bolt on R6/R3, clips allowed)		
	Oil Filter	(Hose Clamp)		
	Oil Filler Cap	(Including dipstick if present, clips allowed)		
	Any Bolts or hose	that carries or retains oil (wire, epoxy or RTV)		
	Radiator Cap	(Clips allowed)		
	Water Drain Bolt	(No Clips)		
	Front Brake Calipe	er Bolts		
	Rear Brake Calipe	r Bolts		
	Front Axel and or A	Axel Nut		
	Front Axel Pinch B	olts (all must be present, one wired per side)		
	Rear Axel Nut			
Cameras				
	Securly Tethered	(No Chin Mount Cameras)		
Brakes & I	Brake Guards			
	Front and Rear Bra	akes Function		
	Front Brake Lever	Guard Installed		
Belly Pan				
,	Removed for Tech	Inspection		
Oil Filter				
	OEM or Approved	Aftermarket Only		
Radiator F		,	_	_
	Only Water, Water	Wetter, Cool Aid and Ice Water (Non-Glyclol Racing Coolant)		
Case Cove	ers			
	Left and Right Afte	ermarket Case Covers		
Side Stand	d/Center Stand	d .		
	Removed			
Toe Guard	/Shark Fin			
	Installed			
Helmet			—	_
	Manufacture date	within 5 years and visible		
		05 or Snell approved full face beliet with no impact damage	$\overline{\Box}$	



Name:	
Tech Inspection:	
-	

Utah Street GP Tech Inspection Checklist

Motorcycle)	Racer Check	Tech Check
	Headlights, taillight and signals taped to not be seen		
	Mirrors (or any other glass) removed or taped over		
	NO FLUID LEAKS - Engine in good running condition		
	Tires in good condition (50% tread remaining or more)		
	Chain/sprocket properly tightened and in good condition		
	All controls properly adjusted		
	All nuts, bolts and fasteners properly tight		
	Brake pads in good condition with plenty of wear left		
	Wheel weights taped with duct tape		
	Valve stem caps / covers installed		
	Any non-OEM parts properly installed and present NO safety hazards		
	Kickstand safely remains in retracted position		
Cameras			
	Securly Tethered (No Chin Mount Cameras)		
Oil Filter			
	OEM or Approved Aftermarket Only		
Radiator F	luid		
	Ethylene Glycol (typical antifreeze) flushed from system & replaced with		
	Distilled Water, Water Wetter or approved racing coolant		
Gear Inspe	ection		
_	Full Coverage Leathers (may be 2-piece suit attached with minimum 3/4 zipper around w	ε <u></u>	
	Leather Motorcycle Gloves that extend above wrist		
	Leather Motorcycle boots fully covering the ankles		
Helmet			
	Manufacture date within 5 years and visible		
	DOT, BSI, ECE-2205 or Snell approved full face helmet with no impact damage		



Race Number:	 		
Name:			

Utah SBA Super Street Bike Tech Inspection Checklist

Motorcycl	e		Racer Check	Tech Check
	Neat and clean, bo	odywork properly installed		
	Headlights, tailligh	t and signals taped & disconnected, but NOT removed		
	Mirrors taped or re	emoved		
	Chain "continuous	rivit" or master link safety wired or RTV on Clip		
	Operational Kill Sv	vitch or button		
	Self-Closing Throt	tle		
	Kick-starter must b	pe secured at two (2) points		
Safety Wi	re			
	Oil Drain Bolt	(including upper oil galley bolt on R6/R3, clips allowed)		
	Oil Filter	(Hose Clamp)		
	Oil Filler Cap	(Including dipstick if present, clips allowed)		
	Any Bolts or hose	that carries or retain oil (wire, epoxy or RTV)		
	Radiator Cap	(Clips allowed)		
	Water Drain Bolt	(No Clips)		
	Front Brake Calipe	er Bolts		
	Rear Brake Calipe	er Bolts		
	Front Axel and or	Axel Nut		
	Front Axel Pinch E	solts (all must be present, one wired per side)		
	Rear Axel Nut (sat	ety wire or cotter pin)		
Cameras				
	Securly Tethered	(No Chin Mount Cameras)		
Brakes &	Brake Guards			
	Brake pads in goo	d condition with plenty of wear left		
Tires		•	_	
11100	DOT-Approved St	reet tires only in good condition		
	Valve Stem Cover	• •		
	Wheel weights Tap		H	
Oil Filter	TTHOOL Worging Tay			
On I liter	OEM or Approved	Aftermarket Only		
Dadietes F	OEM or Approved	Altermarket Only		
Radiator F				
	•	Wetter, Cool Aid and Ice Water (Non-Glyclol Racing Coolant)		
Side Stan	d/Center Stand	1	_	_
	Center or side star	nds secured with safety wire		
Helmet				
	Manufacture date	within 5 years and visible		
	DOT, BSI, ECE-22	205 or Snell approved full face helmet with no impact damage		